

ConTEXt

title : ConTEXt User Module
subtitle : Fullpage documents
author : Wolfgang Schuster
date : January 26, 2011

Introduction

The `fullpage` module is a port of the \LaTeX package with the same name. The module was written after Mohammed Bana asked on the `CONTEX`T mailing list if a module with the same function as the \LaTeX package is available for `CONTEX`T.

The purpose of the module is to easily change the margins of all four margins of the page to the same value without the need of `\setuplayout` in the document.

Fullpage documents

Usage

To use the module you have to load it with the `\usemodule` command. Parameters for the module can be either set with the `\setupfullpage` command or as argument to `\usemodule` when you load the module for your document.

An example how to use the module is:

```
\usemodule[fullpage] [style={cm,empty}]

\starttext
\input knuth
\stoptext
```

You can give for `\usemodule` the same argument as you can give to `\setupfullpage`, which has the following syntax:

```
\setupfullpage [...,*=*,...]

* style = in cm margin plain headings empty none
  margin = DIMENSION
```

The meaning of the values for the “style” key is:

in	set the margins to 1in
cm	set the margins to 1.5cm
margin	set the margins to the “margin” value
plain	no header and narrow footer with 0.5cm
headings	narrow header and footer with 0.5cm
empty	no header and footer

The “margin” value is only useful when you use also the margin key which expects a dimension as argument because its default value is 0pt which result otherwise in no margins at all. You can see the result of all combinations of the style argument at page 5, the examples for the margin argument use a value of 4cm for the margin key.

Fullpage documents

Examples



none



headings



plain



empty



in



in + headings



in + plain



in + empty



cm



cm + headings



cm + plain



cm + empty



margin



margin + headings



margin + plain



margin + empty

