

# RULES

HANS HAGEN

A CONTEXT MKIV MANUAL

## Introduction

This manual describes just one type of rules: those that somehow magically are bound to the typeset text. We will mention a few mechanisms that relate to this in the sense that they share some of the underlying code and logic. The term “rules” should be interpreted liberally as we can kick in some MetaPost which then can get us away from straight rules.

This manual will not be that extensive, after all these mechanisms are not that complex to configure.

## Underlining and overstriking

Already in ConT<sub>E</sub>Xt MkII we had underlining available but with some limitations. We could handle more than one word but at some point you hit the limits of the engine. The MkIV implementation is more flexible. In fact you can underline a whole document (which was actually a request from a user). This feature was also used by a colleague who was experimenting with texts for dyslectic readers.

This mechanism is generic in the sense that a framework is provided to define rules that run alongside text. Take this:

```
\underbars {drawing \underbar{bars} under words is a typewriter leftover}
\overstrikes {striking words makes them \overstrike {unreadable} but
sometimes even \overbar {top lines} come into view.}
```

This shows up as:

drawing bars under words is a typewriter leftover ~~striking words makes them unreadable but~~  
sometimes even top lines come into view.

We can best explain what happens by looking at how these commands are defined:

```
\definebar[overbar] [method=1,dy=0.4, offset=1.8, continue=yes]
\definebar[underbar] [method=1,dy=-0.4,offset=-0.3,continue=yes]
\definebar[overstrike][method=0,dy=0.4, offset=0.5, continue=yes]
```

```
\definebar
[underline]
[method=0,
offset=1.375,
rulethickness=2.5,
continue=yes,
order=background]
```

```
\definebar[overbars] [overbar] [continue=no]
\definebar[underbars] [underbar] [continue=no]
\definebar[overstrikes] [overstrike] [continue=no]
\definebar[understrikes][underline][continue=no]
```

The formal definitions of the commands are show in definition 1 and 2.

```

\definebar [1...] [2...] [3...=...=...]
           OPT      OPT
1  NAME
2  NAME
3  inherits: \setupbar

```

**Definition 1** \definebar

```

\setupbar [1...,...=] [2...,...=]
          OPT
1  NAME
2  color          = COLOR
   continue      = yes no all
   empty         = yes no
   unit          = ex em pt in cm mm sp bp pc dd cc nc
   order         = foreground background
   rulethickness = DIMENSION
   method        = NUMBER
   offset        = NUMBER
   dy            = NUMBER
   max           = NUMBER
   foregroundstyle = STYLE COMMAND
   foregroundcolor = COLOR
   mp            = NAME
   left          = TEXT
   right         = TEXT

```

**Definition 2** \setupbar

The `dy` parameter specifies the shift up or down. The `offset` defines how nested bars are shifted. The `method` determines centering of the bar: we set it to zero when we want an overstrike. The `continue` parameter is responsible for drawing over spaces and the `order` determines the layering.

The units are either hard coded values like points or relate to the font at the spot of the bar. Here are some examples:

```

\setupbars[unit=mm,rulethickness=1]   bar \underbar{foo} bar\quad
\setupbars[unit=ex,rulethickness=1]   bar \underbar{foo} bar\quad
\setupbars[unit=pt,rulethickness=1]   bar \underbar{foo} bar\quad
\setupbars[unit=pt,rulethickness=10pt] bar \underbar{foo} bar

```

bar foo bar   bar foo bar   bar foo bar   bar foo bar

As if underlining wasn't already bad enough, of course at some point there came a request for dashed lines.

```

test \underrandoms{test me} and \underrandom{test} or \underrandom{grep}
test \underdashes {test me} and \underdash {test} or \underdash {grep}
test \underdots {test me} and \underdot {test} or \underdot {grep}

```

The above variants are predefined and render as:

test test me and test or grep  
 test test me and test or grep  
 test test me and test or grep

A graphic is defined as follows. It boils down to drawing one or more shapes. In this example we also force a specific boundingbox so that the result gets positioned right.

```
\startuseMPgraphic{rules:under:...}
  draw
    ((0,RuleDepth) -- (RuleWidth,RuleDepth))
    shifted (0,RuleFactor*RuleOffset)
    withpen pencircle scaled RuleThickness
    withcolor RuleColor ;
  setbounds currentpicture to unitsquare xysized(RuleWidth,RuleHeight) ;
\stopuseMPgraphic
```

The following variables are available:

variable	type	meaning
RuleDirection	string	the direction of the line
RuleOption	string	whatever the caller finds useful
RuleWidth	number	the requested width of the rule
RuleHeight	number	the requested height of the rule
RuleDepth	number	the requested depth of the rule
RuleThickness	number	the linewidth
RuleFactor	number	the set factor (e.g. an ex)
RuleOffset	number	an (optional) offset in case of nesting
RuleColor	color	the color

The RuleFactor can be used as multiplier for the RuleOffset. Later we will see an example of how to use the RuleDirection and RuleOption.

The extra under commands are defined as follows. Watch the mp parameter: it refers to a graphic.

```
\definebar
  [undergraphic]
  [mp=rules:under:dash,
  offset=-.2,
  order=background]

\definebar[underrandom] [undergraphic][mp=rules:under:random]
\definebar[underrandoms][underrandom] [continue=yes]

\definebar[underdash] [undergraphic][mp=rules:under:dash]
\definebar[underdashes] [underdash] [continue=yes]

\definebar[underdot] [undergraphic][mp=rules:under:dots]
\definebar[underdots] [underdot] [continue=yes]
```

A nasty side effect of the implementation is that because we look mostly at glyphs, optionally separated by glue or kern some text might get unseen and therefore not treated.

```
\underbars{We see this \high{\tfxx ®} symbol \runninghbox to 1cm{\hss} often.}
\underbar {We see this \high{\tfxx ®} symbol \runninghbox to 1cm{\hss} often.}
```

This gives:

We see this ® symbol \_\_\_\_\_ often.  
We see this ® symbol \_\_\_\_\_ often.

A running box is seen as text. As you (probably) expect, a nested ornamental rule is supported as well:

```
\underbars
{We see this \high{\tfxx\underdot{®}} symbol \runninghbox to 1cm{\hss} often.}
\underbar
{We see this \high{\tfxx\underdot{®}} symbol \runninghbox to 1cm{\hss} often.}
```

This time we get (you might need a magnifier to see it):

We see this ® symbol \_\_\_\_\_ often.  
We see this ® symbol \_\_\_\_\_ often.

We end this section with an extreme example:

```
\definebar
[xbarone]
[text=\lower\exheight\hbox{\darkred \infofont +},
repeat=yes]
\definebar
[xbartwo]
[text=\lower\exheight\hbox{\darkblue\infofont +},
repeat=yes,
continue=yes]
```

```
Klein : \xbarone{\samplefile {klein}\removeunwantedspaces}\par
Sapolsky : \xbartwo{\samplefile{sapolsky}\removeunwantedspaces}\par
```

Klein : We don't go into a state of shock when something big and bad happens; it has to be something big and bad *that we do not yet understand*. A state of shock is what results when a gap opens up between events and our initial ability to explain them. When we find ourselves in that position, without a story, without our moorings, a great many people become vulnerable to authority figures telling us to fear one another and relinquish our rights for the greater good.

Sapolsky : Agriculture is a fairly recent human invention, and in many ways it was one of the great stupid moves of all time. Hunter-gatherers have thousands of wild sources of food to subsist on. Agriculture changed that all, generating an overwhelming reliance on a few dozen domesticated food sources, making you extremely vulnerable to the next famine, the next locust infestation, the next potato blight. Agriculture allowed for stockpiling of surplus resources and thus, inevitably, the unequal stockpiling of them — stratification of society and the invention of classes. Thus, it allowed for the invention of poverty. I think that the punch line of the primate-human difference is that when humans invented poverty, they came up with a way of subjugating the low-ranking like nothing ever seen before in the primate world.

## Shifting

We mention shifting here because it shares code with the bars. There are two shifts defined but you can define more:

```
\defineshift
[shiftup]
[method=0,
dy=-1,
unit=ex,
continue=yes,
style=\ttx]
```

```
\defineshift
[shiftdown]
[method=1,
dy=.3,
unit=ex,
continue=yes,
style=\ttx,
color=]
```

An example of using the commands defined this way is:

Let's go `\shiftup{up}` and `\shiftdown{down}` a bit!

or: Let's go <sup>up</sup> and <sub>down</sub> a bit! Here we just shift words but you can shift more than that although I haven't yet seen a useful example of that:

We can `\shiftup {\samplefile{tufte}}` whole paragraphs if we really want.

We can We thrive in information-thick worlds because of our marvelous and everyday capacity to select, edit, single out, structure, highlight, group, pair, merge, harmonize, synthesize, focus, organize, condense, reduce, boil down, choose, categorize, catalog, classify, list, abstract, scan, look into, idealize, isolate, discriminate, distinguish, screen, pigeonhole, pick over, sort, integrate, blend, inspect, filter, lump, skip, smooth, chunk, average, approximate, cluster, aggregate, outline, summarize, itemize, review, dip into, flip through, browse, glance into, leaf through, skim, refine, enumerate, glean, synopsisize, winnow the wheat from the chaff and separate the sheep from the goats. whole paragraphs if we really want.

The formal definitions are given in definition 3, 4 and 5. The `align` switch is there for directional (and testing) purposes and is normally not used (or even useful in a line). The `dy` is multiplied by the factor that itself can depend on the used font.

```
\defineshift [1...] [OPT...] [OPT...3...]
```

- 1 NAME
- 2 NAME
- 3 inherits: `\setupshift`

**Definition 3** `\defineshift`

```

\setupshift [...1,...] [...2,...]
                OPT
1  NAME
2  continue = yes no
   unit     = ex em pt in cm mm sp bp pc dd cc nc
   method   = NUMBER
   dy       = NUMBER
   align    = inherits: \setupalign
   style    = STYLE COMMAND
   color    = COLOR

```

**Definition 4** \setupshift

```

\startshift [...*] ... \stopshift
*  NAME

```

**Definition 5** \startshift

## Fillers

The possibility of line fillers was mentioned by Mojca on the ConT<sub>E</sub>Xt mailing list and it's actually not that hard to implement them. The only need I ever had for it was to fill out lines on some legal form and that was actually just some fun challenge in MkII times. The code got lost and never made it into ConT<sub>E</sub>Xt. This time it was added as a side effect of a thread at the tenth ConT<sub>E</sub>Xt meeting.

The idea is to fill the rest of a line with some kind of (ornamental) rule. I'm not sure what sense it makes, even in legal documents. If it is to prevent additions then one should wonder if additions at the end of a (kind of arbitrary) broken line is what we should be afraid of most. So, for now, let's consider it an educational feature.

```

\definelinefiller
  [filler-1]
  [height=.75\exheight,
   distance=.25\emwidth,
   rulethickness=.25\exheight,
   textcolor=darkyellow,
   before=\blank,
   after=\blank,
   color=darkred]

\startlinefiller[filler-1]
  \samplefile{ward}
\stoplinefiller

```

Here we define a filler. As you can see, a rule gets added at the end of a paragraph.

The Earth, as a habitat for animal life, is in old age and has a fatal illness. Several, in fact. It would be happening whether humans had ever evolved or not. But our presence is like the

effect of an old-age patient who smokes many packs of cigarettes per day—and we humans are the cigarettes. 

This time we don't justify:

```
\startalign[flushleft,broad]
  \startlinefiller[filler-1]
    \samplefile{ward}
  \stoplinefiller
\stopalign
```

Now more lines get a rule appended:

The Earth, as a habitat for animal life, is in old age and has a fatal illness. Several, in fact. It  would be happening whether humans had ever evolved or not. But our presence is like the  effect of an old-age patient who smokes many packs of cigarettes per day—and we humans are the cigarettes. 

Before we continue it must be noted that the environment creates a paragraph. If you don't want that you need to use `\setlinefiller` instead. Next we show a middle alignment:

 The Earth, as a habitat for animal life, is in old age and has a fatal illness.   
 Several, in fact. It would be happening whether humans had ever evolved or   
 not. But our presence is like the effect of an old-age patient who smokes   
 many packs of cigarettes per day—and we humans are the cigarettes. 

Let's add another level of complexity, left- and right skips:

```
\startalign[middle]
  \startnarrower
    \startlinefiller[filler-1]
      \samplefile{ward}
    \stoplinefiller
  \stopnarrower
\stopalign
```

Here we get:

 The Earth, as a habitat for animal life, is in old age and has a fatal illness.   
 Several, in fact. It would be happening whether humans had ever evolved   
 or not. But our presence is like the effect of an old-age patient who smokes   
 many packs of cigarettes per day—and we humans are the cigarettes. 

The lines stay within the narrower boundaries but you can extend them to the margins if you like:

```
\startalign[middle]
  \startnarrower
    \startlinefiller[filler-1][scope=global]
      \samplefile{ward}
    \stoplinefiller
  \stopnarrower
```

`\stopalign`

This looks like:

```

████████ The Earth, as a habitat for animal life, is in old age and has a fatal illness. ██████████
████████ Several, in fact. It would be happening whether humans had ever evolved ██████████
████████ or not. But our presence is like the effect of an old-age patient who smokes ██████████
████████ many packs of cigarettes per day—and we humans are the cigarettes. ██████████

```

You can also use a left or right scope, as in:

```

\startalign[middle]
  \startnarrower
    \startlinefiller[filler-1][scope=right]
      \samplefile{ward}
    \stoplinefiller
  \stopnarrower
\stopalign

```

Only the right rules extend into the margins.

```

████████ The Earth, as a habitat for animal life, is in old age and has a fatal illness. ██████████
████████ Several, in fact. It would be happening whether humans had ever evolved ██████████
████████ or not. But our presence is like the effect of an old-age patient who smokes ██████████
████████ many packs of cigarettes per day—and we humans are the cigarettes. ██████████

```

You can get rid of the left rules:

```

\startalign[middle]
  \startnarrower
    \startlinefiller[filler-1][scope=right,location=right]
      \samplefile{ward}
    \stoplinefiller
  \stopnarrower
\stopalign

```

So:

```

    The Earth, as a habitat for animal life, is in old age and has a fatal illness. ██████████
    Several, in fact. It would be happening whether humans had ever evolved ██████████
    or not. But our presence is like the effect of an old-age patient who smokes ██████████
    many packs of cigarettes per day—and we humans are the cigarettes. ██████████

```

Of course these rules are somewhat boring so let's now kick in some MetaPost.

```

\setuplinefiller
  [filler-1]
  [mp=rules:filler:demo,
  %threshold=.25\emwidth,
  color=darkred]

\startuseMPgraphic{rules:filler:demo}

```

```

drawarrow
  if RuleDirection == "TRT" : reverse fi
    ((0,RuleHeight) -- (RuleWidth,RuleHeight))
  withpen
    pencircle scaled RuleThickness
  withcolor
    if RuleOption == "left" : complemented fi RuleColor ;
setbounds currentpicture to
  unitsquare xysized(RuleWidth,RuleHeight) ;
\stopuseMPgraphic

```

The previous example now looks like:

The Earth, as a habitat for animal life, is in old age and has a fatal illness.   
Several, in fact. It would be happening whether humans had ever evolved   
or not. But our presence is like the effect of an old-age patient who smokes   
many packs of cigarettes per day—and we humans are the cigarettes. 


This time we also change the direction and we can let the MetaPost graphic adapt to that by reverting the arrows.

```

\startalign[middle,r2l]
  \startnarrower[4*middle]
    \startlinefiller[filler-1] [scope=global]
      \samplefile{ward}
    \stoplinefiller
  \stopnarrower
\stopalign

```

The direction TRT is T<sub>E</sub>X speak for a right-to-left direction. We use a latin script example for convenience.

 lataf a sah dna ega dlo ni si ,efil lamina rof tatibah a sa ,htraE ehT   
 rehtehw gnineppah eb dluow tI .tcaf ni ,lareveS .ssenlli   
 ekil si ecneserp ruo tuB .ton ro devlove reve dah snamuh   
 fo skcap ynam sekoms ohw tneitap ega-dlo na fo tceffe eht   
 .setteragic eht era snamuh ew dna—yad rep setteragic 

The next rendering shows what happens when we set `\parindent` and `\parfillskip` to an excessive have a 100pt.

 ega dlo ni si ,efil lamina rof tatibah a sa ,htraE ehT   
 rehtehw gnineppah eb dluow tI .tcaf ni ,lareveS .ssenlli lataf a sah dna   
 fo tceffe eht ekil si ecneserp ruo tuB .ton ro devlove reve dah snamuh   
 —yad rep setteragic fo skcap ynam sekoms ohw tneitap ega-dlo na   
 .setteragic eht era snamuh ew dna 

Here we have adapted the graphic a bit:

```

if RuleDirection == "TRT" : reverse fi
  if RuleOption == "right" : reverse fi
    ((0,RuleHeight) -- (RuleWidth,RuleHeight))

```

```
\definelinefiller [...1] [...2] [...3...OPT...OPT]
```

1 NAME  
2 NAME  
3 inherits: \setuplinefiller

**Definition 6** \definelinefiller

```
\setuplinefiller [...1...OPT] [...2...OPT]
```

1 NAME  
2 location = left right both  
scope = left right local  
mp = NAME  
height = DIMENSION  
depth = DIMENSION  
distance = DIMENSION  
threshold = DIMENSION  
rulethickness = DIMENSION  
before = COMMAND  
after = COMMAND  
color = COLOR  
textstyle = STYLE COMMAND  
textcolor = COLOR  
align = inherits: \setupalign

**Definition 7** \setuplinefiller

## User rules

Characters and rules are the only graphical elements that T<sub>E</sub>X really knows about. Even if you see images in a document, you should realize that they are just blobs with dimensions and that the backend replaces such blobs by real images.

The primitive operations for rules are \hrule and \vrule and the main difference is to what way they adapt to their situation when no dimensions are given and the mode change they trigger.

```
hrule{\darkred \hrule width 10cm height 3mm depth 2mm}\par
vrule{\darkyellow\vrule width 10cm height 3mm depth 2mm}\par
hrule{\darkred \hrule width 10cm } \par
vrule{\darkyellow\vrule height 3mm depth 2mm}\par
```

```
hrule{\darkred \leaders\hrule height 1mm\relax\hfill}\hrule\par
```

When more text is to follow you should end a specification with \relax to make sure that the scanner stops looking for more arguments. With \leaders you can create flexible rules.

hrule



vrule



hrule



vrule

hrulehrule



In ConT<sub>E</sub>Xt we also have so called frame rules:

```
\color[darkred]{\frule
  width 10cm
  height 1cm
  line 1mm
\relax}
```

This will produce a rectangle:



There are a few more keywords. Keep in mind that we actually have a new kind of primitive here, so we follow the T<sub>E</sub>X conventions of keywords.

```
\ruledhbox\bgroup
  \darkgray
  \frule width 100mm height 10mm depth 8mm radius 2mm line 2pt type fill\relax
  \hskip-100mm
  \darkred
  \frule width 100mm height 10mm depth 8mm radius 2mm line 2pt\relax
  \hskip-100mm
  \hbox to 100mm{\white \bold \hfill some handy word with frames\hfill}%
\egroup
```

Of course this is a rather low level way of doing frames and such, but when you like that kind of low level programming you get the possibility here.



You can combine this with existing mechanisms. Take the following:

```
\defineoverlay[normalframe]
  [\frule
    width \overlaywidth
    height\overlayheight
    line \overlaylinewidth
  ]
```

```
\defineoverlay[ovalframe]
  [\frule
    width \overlaywidth
    height \overlayheight
    line \overlaylinewidth
    radius \overlayradius
  ]
```

This is a variant on the already available round corners:

```
\test test \test \test \test \test \test \test \test \test
```

The above result is accomplished with:

```
\hbox \bgroup
  \framed {test}\quad
  \framed[frame=off] {test}\quad
  \framed[background=normalframe,frame=off]{test}\quad
  \framed[background=normalframe,frame=off]{test}\quad
  \framed[corner=round] {test}\quad
  \framed[corner=round] {test}\quad
  \framed[background=ovalframe,frame=off] {test}\quad
  \framed[background=ovalframe,frame=off] {test}\quad
  \framed[background=ovalframe,frame=on] {test}\quad
  \framed[background=ovalframe,frame=on] {test}\quad
\egroup
```

Given the examples in the previous sections it will be no surprise that we can also use MetaPost.

```
\startuseMPgraphic{demoshape:back}
  fill
    unitcircle xysized (RuleWidth,RuleHeight+RuleDepth)
    withcolor RuleColor ;
\stopuseMPgraphic
```

```
\startuseMPgraphic{demoshape:fore}
  draw
    unitcircle xysized (RuleWidth,RuleHeight+RuleDepth)
    withcolor RuleColor
    withpen pencircle scaled 4RuleThickness ;
\stopuseMPgraphic
```

```
\hbox\bgroup
  \darkgray \frule width 100mm height 10mm depth 8mm type mp line 2pt
    data {\includeMPgraphic{demoshape:back}}
  \relax
  \hskip-100mm
  \darkred \frule width 100mm height 10mm depth 8mm type mp line 2pt
    data {\includeMPgraphic{demoshape:fore}}
  \relax
```

```
\hskip-100mm
\hbox to 100mm{\white \bold \hfill some handy word with frames\hfill}
\egroup
```

Or rendered:



The `\blackrule` command is the more high level way to inject a rule.

```
\blackrule
[width=10cm,
height=1cm,
depth=1cm,
color=darkred]
```


This produces a boring rule:



Again we can revert to MetaPost:

```
\blackrule
[width=10cm,
height=1cm,
depth=1cm,
color=darkred,
type=mp,
mp=demoshape:back]
```

or:



The formal definition of this command is shown in definition 8 and 9.

## Hiding

In education a to be filled in text is often represented by a gap in the running text and the bar drawing mechanism supports this. There is a predefined `\hiddenbar` command:

```
\definebar
```

```
\setupblackrules [...,.*=,....]
```

```
* width      = max DIMENSION
height      = max DIMENSION
depth      = max DIMENSION
distance    = DIMENSION
n           = NUMBER
alternative = a b
style      = STYLE COMMAND
color     = COLOR
type      = mp yes no
mp        = NAME
```

**Definition 8** \setupblackrules

```
\blackrule [...,.*=,....]
```

```
* inherits: \setupblackrulesOPT
```

**Definition 9** \blackrule

```
[hiddenbar] [underbar]
[continue=yes,empty=yes,
left=\zwj,right=\zwj]
```

The Earth, as a habitat for animal life, is in old age and has a fatal illness. Several, in fact. It would be happening whether humans had ever evolved or not. But our presence is like the effect of an old-age patient who smokes many packs of cigarettes per day—and we humans are the cigarettes. \_\_\_\_\_ The Earth, as a habitat for animal life, is in old age and has a fatal illness. Several, in fact. It would be happening whether humans had ever evolved or not. But our presence is like the effect of an old-age patient who smokes many packs of cigarettes per day—and we humans are the cigarettes. \_\_\_\_\_ The Earth, as a habitat for animal life, is in old age and has a fatal illness. Several, in fact. It would be happening whether humans had ever evolved or not. But our presence is like the effect of an old-age patient who smokes many packs of cigarettes per day—and we humans are the cigarettes. \_\_\_\_\_ The Earth, as a habitat for animal life, is in old age and has a fatal illness. Several, in fact. It would be happening whether humans had ever evolved or not. But our presence is like the effect of an old-age patient who smokes many packs of cigarettes per day—and we humans are the cigarettes. \_\_\_\_\_ The Earth, as a habitat for animal life, is in old age and has a fatal illness. Several, in fact. It would be happening whether humans had ever evolved or not. But our presence is like the effect of an old-age patient who smokes many packs of cigarettes per day—and we humans are the cigarettes.

The previous text is generated with:

```
\samplefile{ward}\hiddenbar           {\color[red]{invisible}}
\samplefile{ward}\hiddenbar           {\quad\color[red]{invisible}\quad}
\samplefile{ward}\hiddenbar{\quad\quad\quad\color[red]{invisible}\quad\quad\quad}
\samplefile{ward}\hiddenbar           {\color[red]{invisible}\quad\quad\quad\quad\quad}
\samplefile{ward}
```

Here is a variant that inserts spacing at the left and right edges. In this case the spacing is kept at a linebreak:

```
\definebar
  [widehiddenbar]
  [hiddenbar]
  [left={\quads[3]},
   right={\quads[3]}]

\widehiddenbar{invisible} \samplefile{weisman}
\widehiddenbar{invisible} \samplefile{weisman}
\widehiddenbar{invisible}
```

\_\_\_\_\_ Since the mid-1990s, humans have taken an unprecedented step in Earthly annals by introducing not just exotic flora or fauna from one ecosystem into another, but actually inserting exotic genes into the operating systems of individual plants and animals, where they're intended to do exactly the same thing: copy themselves, over and over. \_\_\_\_\_

Since the mid-1990s, humans have taken an unprecedented step in Earthly annals by introducing not just exotic flora or fauna from one ecosystem into another, but actually inserting exotic genes into the operating systems of individual plants and animals, where they're intended to do exactly the same thing: copy themselves, over and over. \_\_\_\_\_

## Tabulate

The previously discussed mechanism is also available in the tabulate mechanism. We start with simple backgrounds:

```
\starttabulate
  \NL[darkred]    foo \NC bar \NC \NR
  \NL[darkgreen]  foo \NC bar \NC \NR
  \NL[darkblue]   foo \NC \samplefile{tufte} \NC \NR
  \NL[darkgray]   foo \NC bar \NC \NR
  \NL[darkyellow] foo \NC bar \NC \NR
  \LL
\stoptabulate
```

This comes out as:

```
foo bar
foo bar
foo We thrive in information-thick worlds because of our marvelous and everyday capacity to
select, edit, single out, structure, highlight, group, pair, merge, harmonize, synthesize,
focus, organize, condense, reduce, boil down, choose, categorize, catalog, classify, list,
abstract, scan, look into, idealize, isolate, discriminate, distinguish, screen, pigeonhole,
pick over, sort, integrate, blend, inspect, filter, lump, skip, smooth, chunk, average, ap-
proximate, cluster, aggregate, outline, summarize, itemize, review, dip into, flip through,
browse, glance into, leaf through, skim, refine, enumerate, glean, synopsisize, winnow the
wheat from the chaff and separate the sheep from the goats.
foo bar
foo bar
```

There are several two character commands that deal with this:

<b>command</b>	<b>related to</b>	<b>effect</b>	<b>\NL</b>	<b>\NC</b>	<b>Normal with Line</b>
<code>\ND</code>	<code>\NC</code>	Normal with Default Line			
<code>\LB</code>	<code>\BC</code>	Bold with Line			
<code>\DB</code>	<code>\BC</code>	Bold with Default Line			
<code>\NF</code>	<code>\NC</code>	Normal with Filler			
<code>\NP</code>	<code>\NC</code>	Normal with Predefined Filler			
<code>\FB</code>	<code>\BC</code>	Bold with Filler			
<code>\NA</code>	<code>\NC</code>	Normal with Auto Toggled Line			
<code>\BA</code>	<code>\BC</code>	Bold with Auto Toggled Line			

Before we show more, we set up tabulate:

```
\setuptabulate
[blank={small,samepage},
 headstyle=bold,
 rulecolor=darkred,
 rulethickness=1pt,
 background=foo,
 backgroundcolor=darkred,
 foregroundcolor=white]
```

This time we don't set colors in the table itself:

```
\starttabulate[|l|l|]
  \DB foos      \BC bars      \BC \NR
  \TB
  \NC foo foo foo \NC bar bar bar bar \NC \NR
  \NC foo foo foo \NC bar bar bar bar \NC \NR
  \NC foo foo foo \NC bar bar bar bar \NC \NR
  \NC foo foo foo \NC bar bar bar bar \NC \NR
  \LL
\stoptabulate
```

```
foos      bars
foo foo foo  bar bar bar bar
```

---

Instead of coming up with a separate mechanism for hooking in MetaPost we use the linefiller mechanism. We use these graphics:

```
\startuseMPgraphic{foo}
  fill unitsquare
    xyscaled (RuleWidth,RuleHeight+RuleDepth) enlarged (ExHeight/4,ExHeight/8)
    shifted (-ExHeight/8,ExHeight/16)
    withcolor RuleColor ;
\stopuseMPgraphic
```

```

\startuseMPgraphic{bar}
  fill unitsquare
    xyscaled (RuleWidth,RuleHeight+RuleDepth) enlarged (ExHeight/4,ExHeight/8)
    shifted (-ExHeight/8,ExHeight/16)
    randomized ExHeight
    withcolor RuleColor ;
\stopuseMPgraphic

```

With these fillers:

```

\definelinefiller[foo][mp=foo,color=darkgreen]
\definelinefiller[bar][mp=bar,color=darkred]

```

An example of usage is:

```

\linefillerhbox[foo] to 12cm{\hss\strut\white\bf FOO\hss} \blank
\linefillerhbox[bar] to 10cm{\hss\strut\white\bf BAR\hss} \blank
\linefillerhbox[foo] to 9cm{\hss\strut\white\bf FOO\hss} \blank
\linefillerhbox[bar] to 14cm{\hss\strut\white\bf BAR\hss}

```

**FOO**

**BAR**

**FOO**

**BAR**

We can rely on the default:

```

\starttabulate[|||]
  \PB foo          \BC bars          \BC \NR
  \NC foo foo foo \NC bar bar bar bar \NC \NR
  \NC foo foo foo \NC bar bar bar bar \NC \NR
  \NC foo foo foo \NC bar bar bar bar \NC \NR
  \NC foo foo foo \NC bar bar bar bar \NC \NR
\stoptabulate

```

**foo**      **bars**

```

foo foo foo  bar bar bar bar

```

or be explicit:

```

\starttabulate[|||]
  \FB[bar] foos          \BC bars          \BC \NR
  \NC          foo foo foo \NC bar bar bar bar \NC \NR
  \NC          foo foo foo \NC bar bar bar bar \NC \NR
  \NC          foo foo foo \NC bar bar bar bar \NC \NR
  \NC          foo foo foo \NC bar bar bar bar \NC \NR

```

