

NAME

CURLINFO_RESPONSE_CODE – get the last response code

SYNOPSIS

```
#include <curl/curl.h>
```

```
CURLcode curl_easy_getinfo(CURL *handle, CURLINFO_RESPONSE_CODE, long *codep);
```

DESCRIPTION

Pass a pointer to a long to receive the last received HTTP, FTP or SMTP response code. This option was previously known as CURLINFO_HTTP_CODE in libcurl 7.10.7 and earlier. The stored value will be zero if no server response code has been received. Note that a proxy's CONNECT response should be read with *CURLINFO_HTTP_CONNECTCODE(3)* and not this.

Support for SMTP responses added in 7.25.0.

PROTOCOLS

HTTP, FTP and SMTP

EXAMPLE

```
CURL *curl = curl_easy_init();
if(curl) {
    CURLcode res;
    curl_easy_setopt(curl, CURLOPT_URL, "http://example.com");
    res = curl_easy_perform(curl);
    if(res == CURLE_OK) {
        long response_code;
        curl_easy_getinfo(curl, CURLINFO_RESPONSE_CODE, &response_code);
    }
    curl_easy_cleanup(curl);
}
```

AVAILABILITY

Added in 7.10.8. CURLINFO_HTTP_CODE was added in 7.4.1.

RETURN VALUE

Returns CURLE_OK if the option is supported, and CURLE_UNKNOWN_OPTION if not.

SEE ALSO

curl_easy_getinfo(3), *curl_easy_setopt(3)*, *CURLINFO_HTTP_CONNECTCODE(3)*,